

Advantage:

- >> CUMMINS Diesel Engine
- >> Fast Rotation Speed
- >> Wireline Diamond Core Drilling
- >> Hydraulic Clip
- >> 0-1500M Drilling Capacity
- >> High pressure mud pump



JCD1500

CRAWLER DIAMOND CORE DRILLING RIG

JCD1500履带式岩芯钻机

INTRODUCTION产品介绍

- >> JCD1500 Full Hydraulic Portable Drilling Rig is a kind of light rig designed for geological exploration in remote area difficult to enter.
- >> It is mainly suitable for diamond drilling with wire line coring technique. The rig consists of diesel power unit, hydraulic system, control panel, mast, main winch, wireline winch, drill head, feed system, footclamp, etc.
- >> The rig is completely hydraulic driven for all its surface coring function. Fission style design makes the rig in good assemblability and disassemblability, facilitating transportation to most inaccessible areas. Robust structure plus exact control system ensures high penetration rate and outstanding reliability.
- >> JCD1500 can be operated in unconsolidated layer, and the slag can be discharged under by mud,It suitable for drilling complicated geological conditions.
- >> The main drive of rig is hydraulic and the four landing legs and drilling tower are hydraulic controlled. Transfer case and mud pump clutch system are also hydraulic operated.
- >> The rotary head,have two gear,rotation speed have different speed stepless adjustment and the rotary torque is 970-3930Nm.

>> CHARACTERISTICS产品特点

- >> Full Hydraulic and Drill Head model. The drill head rotation is realized with hydraulic pumps driven by diesel engines; this also makes the feeding hydraulic cylinder system realize its full stroke feeding in both higher and lower speed.
- >> Centralized control console is suitable for each manipulation and control. Rapid pulling and lifting reduce the auxiliary time and enhance the work efficiency.
- >> It's a hydraulic rotary drilling rig with directional circulation. It can equipped with BW250 mud pump which adopts the slurry as the washing fluid and can drill on clay, sand and rock if it is equipped with suitable drilling bit.
- >> The power of drilling rig comes from a 164KW CUMMINS engine drives the large displacement high pressure plunger pump and it is characterized by powerful dynamic and stable performance.
- >> With Good dismantlability. The rig is adopted split type in design, including power unit, hydraulic oil tank, manipulation platform and operation mechanism, i.e. the drilling section,The rig can be applied and performed in narrow space for drilling of hole at 45° - 90°



Specification技术参数

Specification	Unit	JCD1500
Drilling Method		Wireline Diamond Core Drilling
Drill depth	m	700,1000,1500
Drilling Diameter		NQ,HQ,PQ
Drill system and operation		Hydraulic
Mobility		Steel Crawler
Mast compensation		Standard
Drive Head		
Rotation torque	Gear-1 Nm	3930-1840
	Gear-2 Nm	2060-970
	Gear-1 Rpm	10-520
Speed	Gear-2 Rpm	20-1000
Drill Tower		
Tower Height	mm	9960
Load Capacity	Kgs	30000
Max. Drill pipe length	m	6
Drilling angle	°	45-90
Feeding mode		Hydraulic Cylinder
Feeding Stroke	mm	3500
Feeding Force	KN	65
Lifting Capacity	KN	170
Main Winch		
Dia. Of wirerope	mm	20
Reel capacity	m	26
Lifting Capacity-Single rope	KN	95
Lifting Capacity-Double rope	KN	190
Lifting Speed-Single rope	M/Min	40
Lifting Speed-Double rope	M/Min	20
Wireline Coring Winch		
Dia. Of wirerope	mm	6
Reel capacity	m	1500
Lifting Capacity	kn	18
Lifting Speed	M/Min	110-200
Diesel engine		
Power	KW	164
Model		CUMMINS
Drill Pipe		
Drill pipe length	m	3-6
Drill pipe diameter		BQ,NQ,HQ,PQ
Mud pump		
Max.Flow capacity	L/Min	220
Max. working pressure	Mpa	3
Weight &Dimensions		
Weight	Kgs	11000
Size(L*W*H)	mm	6500×2290×2550



Main Structure主要结构



Main Configuration 主要配件

				
Brand Name: CUMMINS Brand From: USA Applied Position: Power System	Brand Name: Rexroth Brand From: Germany Applied Position: Magnetic valve Flow Valve	Brand Name: SAUER DAANFOSS Brand From: USA Applied Position: Hydraulic Pump	Brand Name: KTR Brand From: Germany Applied Position: Coupling	Brand Name: EATON Brand From: USA Applied Position: Winch Hydraulic Motor
				
Brand Name: JEIL Brand From: Korea Applied Position: Crawler Motor	Brand Name: SAI Brand From: Italy Applied Position: Mud pump motor Core winch motor	Brand Name: YUCI Hydraulic Brand From: China Applied Position: Hydraulic Cylinder	Brand Name: LEEMIN Brand From: China Applied Position: Filter system	Brand Name: Changjiang Hydraulic Brand From: China Applied Position: Directional control valve

Core Drilling Products

岩心钻进相关产品



Core Drilling Bits



Reaming Shells



Core Barrels




Overshot



Drill Pipe&Casing



Sub



Water Swivel



Hoisting Plug




Circle Wrench



Foot Clamp



Recovery Tools



Core Trays



Rope Winches



Mud Agitator



Instrument



In Project Site
钻孔现场



Contact Us 联系我们

BEIJING JINCHENG MINING TECHNOLOGY CO., LTD

Add: Rm1407, Building A, NO. 13 Beiyuan Road, Chaoyang, Beijing, China

Mob: 0086 13810203890

Tel: 0086 10 84673566

Fax: 0086 10 51617069

Email: sales@jcdrill.com

Web: www.jcdrill.com

WhatsApp/Viber/Wechat: +8613810203890



WECHAT



WHATSAPP



WWW.JCDRILL.COM

Crawler CoreDrilling Rig
履带式岩芯钻机