

GX11FF (15hp)
 Oil-Injected Rotary Screw Compressor
 Air Cooled
Integrated Dryer

SPECIFICATIONS

INLET CONDITIONS

Absolute inlet pressure	psig	14.5
Relative air humidity	%	0
Ambient Temperature	°F	68
FAD	CFM	52
Normal operating pressure	PSIG	125
Minimum operating pressure	PSIG	58
Maximum operating pressure	PSIG	132

POWER INPUT @ 125 PSIG

Power input	kW	9.8
Power input at no load	kW	1.9
Dryer	kW	.86
power consumption at full load		
Amps @ 460v Pack/FF		18/22.6
Motor type		TEFC

COMPRESSOR COOLING

Package cooling air flow	CFM	1377
FF unit cooling air flow	CFM	233
Refrigerant Type (FF only)		R134a
Pressure Dewpoint (FF only)	°F	39
Oil filter life	Hours	4000
Compressor oil life	Hours	8000
Compressor oil sump cap.	GAL	1.3
Sound level	dB (A)	71
Per CAGI PNEUROP PN8NTC2.2 test code		
Tank size	Gallon	80



DIMENSIONS	
Length	60"
Width	25"
Height	56"
Weight	849#
Discharge	1/2" npt

WARRANTY: Atlas Copco warrants that all new stationary compressors and other Products manufactured by Atlas Copco and affiliates shall be free of defects in design, material and workmanship for a period of fifteen (15) months from date of shipment to Purchaser, or twelve (12) months from date of initial start-up, whichever occurs first. For a full description of the warranty please see Atlas Copco's Terms and Conditions of sale.

EXTENDED 5 YEAR WARRANTY

Atlas Copco warrants that the major components on new air compressors, (**air end, main drive motor, oil cooler, after cooler, and oil separator tank**) will be free of defects in material or workmanship for a period of 5 years, provided the customer has met the standard preventive maintenance service schedule according to Atlas Copco recommendation.