



The Sullair Portable Air Compressor

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- E-Z lube axle
- Large tool box compartment
- Curbside instrument panel
- SSAM–Shutdown System and Annunciation Module
- Battery disconnect switch
- Idle warm-up valve
- Emergency stop
- Rocker type start switch
- Protective shutdown switches
- Fuel/Water separator
- Three-Stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Durable powder coat finish
- Wide track
- Galvanneal sheet metal
- Recessed tail lights
- Rear bumper



Total Accessibility
Routine maintenance is simplified.



Large Tool Box
Compartment Sullair
pneumatic tool sold
separately.



Rotary Screw Compressor
by Sullair
The pioneer in rotary screw
technology.



Sullair AWF Compressor
Fluid Improved hot and cold
weather lubrication. Longer
compressor fluid life.
Extended air end warranty.



Model	UNIT	750XH
Complete Machine	Double-Flighted Screw/Portable	
Nominal volume flow	m ³ /min(CFM)	21.2(750)
Rated Discharge Pressure	bar/psi	13.8(200)
Working pressure range	bar/psi	5.5-13.8
Sound Power Levels	dBA	79
Max.Tract speed	km/h	35
Max.working angle	°	15
Weight	kg/Lb	4620
Length X Width X Height	mm	3.74X2.21X2.2
Tire	PR	7.50-16-14PR
Tire Pressure	kPa	630-700
Rated Altitude	m/ft	4267(14000)
Diesel Engine		
Manufacturer	CUMMINS	CUMMINS
Type	6BT5.9-C	M11-C300
Working Speed rpm)	full /no load	2100/1400
Rated Output Power	KW/Ps	224(300)
Displacement	L/in	10.8
Coolant Volume	L/U.S.gal	60(16)
Oil Capacity	L/U.S.gal	33(8.7)
Fuel Tank Capacity	L/U.S.gal	398(105)
Voltage of Electric System	V	24
Rated capacity of Battery	Ah/ca.	210
Air Compressor		
Lubricant Capacity	L/U.S.gal	94.5(25)
Q'ty & Spe of air supply valve		(1)2",(2)1",(1)1/2"

