



The Sullair Portable Air Compressor

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- E-Z lube axle
- Large tool box compartment
- Curbside instrument panel
- SSAM–Shutdown System and Annunciation Module
- Battery disconnect switch
- Idle warm-up valve
- Emergency stop
- Rocker type start switch
- Protective shutdown switches
- Fuel/Water separator
- Three-Stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Durable powder coat finish
- Wide track
- Galvanneal sheet metal
- Recessed tail lights
- Rear bumper



Total Accessibility
Routine maintenance is simplified.



Large Tool Box
Compartment Sullair
pneumatic tool sold
separately.



Rotary Screw Compressor
by Sullair
The pioneer in rotary screw
technology.



Sullair AWF Compressor
Fluid Improved hot and cold
weather lubrication. Longer
compressor fluid life.
Extended air end warranty.



Model	UNIT	900XH
Complete Machine		
Nominal volume flow	m3/min(CFM)	24/350
Rated Discharge Pressure	bar/psi	9.7-24/140-350
Working pressure range	bar/psi	25.5/900
Max.Tract speed	km/h	35
Max.working angle		15°
Weight	kg/Lb	7200
Length X Width X Height	mm	5025X2200X2400
Trackwidth	mm(in)	1835/72.2
Tire		7.50-16-14PR
Tire Pressure	kPa	630-700
Diesel Engine		
Manufacturer	CAT	CAT
Type	C-12	C-12
Working Speed (rpm)	full /no load	1800/1300
Rated Output Power	KW/HP	317/425
Displacement	L/in	11.95/729
Coolant Volume	L/U.S.gal	47.4/12.5
Oil Capacity	L/U.S.gal	30/7.9
Fuel Tank Capacity	L/U.S.gal	600/158.5
Voltage of Electric System	V	24
Rated capacity of Battery	Ah/ca.	210Ah/ea.
Air Compressor		
Lubricant Capacity	L/U.S.gal	98/25.9
Q'ty & Spe of air supply valve		(2)2"(1)1"(1)1/2"

