



The Sullair Portable Air Compressor

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- E-Z lube axle
- Large tool box compartment
- Curbside instrument panel
- SSAM–Shutdown System and Annunciation Module
- Battery disconnect switch
- Idle warm-up valve
- Emergency stop
- Rocker type start switch
- Protective shutdown switches
- Fuel/Water separator
- Three-Stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Durable powder coat finish
- Wide track
- Galvanneal sheet metal
- Recessed tail lights
- Rear bumper



Total Accessibility
Routine maintenance is simplified.



Large Tool Box
Compartment Sullair
pneumatic tool sold
separately.



Rotary Screw Compressor
by Sullair
The pioneer in rotary screw
technology.



Sullair AWF Compressor
Fluid Improved hot and cold
weather lubrication. Longer
compressor fluid life.
Extended air end warranty.



MDOEL	UNIT	1070XH
Complete Machine		
Nominal volume flow	m3/min(CFM)	30.3/1070
Rated Discharge Pressure	bar/psi	24.1/350
Working pressure range	bar/psi	9.7-24.1
Max.Tract speed	km/h	35
Max.working angle	°	15
Sound Power Levels	dBA	83
Weight	kg	6670
Length X Width X Height	mm	4684*2100*2360
Trackwidth	mm	1817
Tire		8.25-16-14PR
Tire Pressure	kPA(psi)	690-760(100-110)
Diesel Engine		
Manufacturer	CUMMINS	CAT
Type		3406C
Working Speed full /no load	rpm	1750/1300
Rated Output Power	KW/BHP	347/465
Displacement	L/in3	14.6/893
Coolant Volume	L/U.S.gal	34.1/9
Oil Capacity	L/U.S.gal	Oct-38
Fuel Tank Capacity	L/U.S.gal	700/185
Fuel consumption(full load)	L/h(U.S.gal)	82/21.7
Voltage of Electric System	V	24
Rated capacity of Battery	Ah/ca.	210Ah/ea.
Air Compressor		
Lubricant Capacity	L/U.S.gal	60/15.8
Q'ty & Spe of air supply valve		1rp2,1rp3/4

