



The Sullair Portable Air Compressor

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- E-Z lube axle
- Large tool box compartment
- Curbside instrument panel
- SSAM–Shutdown System and Annunciation Module
- Battery disconnect switch
- Idle warm-up valve
- Emergency stop
- Rocker type start switch
- Protective shutdown switches
- Fuel/Water separator
- Three-Stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Durable powder coat finish
- Wide track
- Galvanneal sheet metal
- Recessed tail lights
- Rear bumper



Total Accessibility
Routine maintenance is simplified.



Large Tool Box
Compartment Sullair
pneumatic tool sold
separately.



Rotary Screw Compressor
by Sullair
The pioneer in rotary screw
technology.



Sullair AWF Compressor
Fluid Improved hot and cold
weather lubrication. Longer
compressor fluid life.
Extended air end warranty.



MDOEL	UNIT	900H
Complete Machine	m3/min(CFM)	
Nominal volume flow	bar/psi	25.5/900
Rated Discharge Pressure	bar/psi	10.3/150
Working pressure range	dBa	5.5/10.3
Sound Power Levels	dBa	110
Max.Tract speed	kg/Lb	35
Max.working angle	mm	15°
Weight	kg	4620
Length X Width X Height	PR	3740X2210X2200
Tire	kPa	7.5-16-14PR
Tire Pressure	m/ft	630-700
Diesel Engine		
Manufacturer	CUMMINS	CUMMINS
Type	6BT5.9-C	M11-C300
Working Speed rpm)	full /no load	2100/1400
Rated Output Power	KW/Ps	224/300
Displacement	L/in	10.8
Coolant Volume	L/U.S.gal	
Oil Capacity	L/U.S.gal	33/8.7
Fuel Tank Capacity	L/U.S.gal	398/105
Fuel consumption(full load)	L/h(U.S.gal)	
Voltage of Electric System	V	24
Rated capacity of Battery	Ah/ca.	210Ah/ea.
Air Compressor		
Lubricant Capacity	L/U.S.gal	94.5/25
Q'ty & Spe of air supply valve		(1)2"(2)1",(1)1/2"

