



## The Sullair Portable Air Compressor

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- E-Z lube axle
- Large tool box compartment
- Curbside instrument panel
- SSAM–Shutdown System and Annunciation Module
- Battery disconnect switch
- Idle warm-up valve
- Emergency stop
- Rocker type start switch
- Protective shutdown switches
- Fuel/Water separator
- Three-Stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Durable powder coat finish
- Wide track
- Galvanneal sheet metal
- Recessed tail lights
- Rear bumper



Total Accessibility  
Routine maintenance is simplified.



Large Tool Box  
Compartment Sullair  
pneumatic tool sold  
separately.



Rotary Screw Compressor  
by Sullair  
The pioneer in rotary  
screw technology.



Sullair AWF Compressor Fluid  
Improved hot and cold weather  
lubrication. Longer compressor  
fluid life. Extended air end  
warranty.



MDOEL	UNIT	1070XHH
<b>Complete Machine</b>		
Nominal volume flow	m3/min(CFM)	30.3/1070
Rated Discharge Pressure	bar/psi	34.5/500
Working pressure range	bar/psi	13.8-34.5
Max.Tract speed	km/h	35
Max.working angle	°	15
Sound Power Levels	dB(A)	83
Weight	kg	7300
Length X Width X Height	mm	4680*2100*2490
Trackwidth	mm	1817
Tire		8.25-16-14PR
Tire Pressure	kPA(psi)	690-760(100-110)
<b>Diesel Engine</b>		
Manufacturer	CUMMINS	CATERPILLAR
Type		C15 ACERT Tier3
Working Speed full /no load	rpm	1800/1300
Rated Output Power	KW/BHP	403/540
Displacement	L/in3	15.2/927.6
Coolant Volume	L/U.S.gal	60/15.9
Oil Capacity	L/U.S.gal	40.3/10.6
Fuel Tank Capacity	L/U.S.gal	700/185
Fuel consumption( full load)	L/h(U.S.gal)	82/21.7
Voltage of Electric System	V	24
Rated capacity of Battery	Ah/ca.	210Ah/ea.
<b>Air Compressor</b>		
Lubricant Capacity	L/U.S.gal	60/15.8
Q'ty & Spe of air supply valve		1rp2,1rp3/4

